Commonwealth of Kentucky Energy and Environment Cabinet Department for Environmental Protection

DIVISION FOR AIR QUALITY

DEP7007K

SURFACE COATING (OR) PRINTING OPERATION

SECTIO	ON I G	SENERAL				-		
	Emission I			Pro	posed/Actual Sta	rt of Construct	ion:	
	Check Poll	lutants Emitted: CO	B. NO _x	C.	\square SO ₂		D. VOCs	
	E.	M or PM ₁₀	If E is checked		Condensable	le Organic	☐ Non-Volatile	
	F. H	IAPs	If F is checked		☐ Volatile		☐ Non-Volatile	
	G. L	ead	H. Fluoride	I.	Other Poter	ntially Hazardo	ous Pollutants (specify)	
		on of the Emissi scribe the emissi		y componei	nts (machinery), i	including the n	umber of applicators:	
	Describe ra	aw material into	the process (includ	ing the surf	ace coated):			
	Describe th	he resulting proc	luct from the unit: _					
4)	ATTACH including ai	A PROCESS I irborne contamina	FLOW DIAGRAM nts and other waste m	I. Show entraterials, all p	ry and exit points or process equipment,	f all materials an control equipme	nd finished products. Label all mater ent and stacks/vents.	ials
This cate	A.	Auto or Light-dut Large Appliance of Severage Can Co Miscellaneous Mo Coating of Plastic Sabric, Vinyl, or I Sincludes:	ating etal Parts Coating e Parts for Business Paper Coating 1. Magnet To 2. Pressure S ng rotogravure & Fl 1. Flexible V	Machines ape Coating Sensitive Ta exographic inyl and Un	pe & Label Coat Printing rethane Coating o	☐ Metal C☐ Magnet☐ Flat Wo	urniture Coating oil Coating Wire Insulation Coating ood Panel Coating	
			utions in Chapters 5 ories and possible r			l of Kentucky F	Administrative Regulations for	
6) Typ	e and amo		solvent(s) used at t			direct result o	of the emission point's operation	n:
	Type:		N	Aaximum U	sage:	gal/day		

Commonwealth of Kentucky Natural Resources & Environmental Protection Cabinet Department for Environmental Protection

DIVISION FOR AIR QUALITY

DEP7007K

Continued

SURFACE COATING (OR) PRINTING OPERATION

	ON II APPLICATOR DATA te the following for each applicator. Make additional copies of this section as required. If multiple applicators are essentially l, the data may be combined on one copy by identifying multiple applicators in the field provided											
7)	Identity: Emission Point #: Applicator #: Function of the Applicator:											
8)	Type of Applicator (Check the appropriate type):											
	A. Spray: Air Gun Airless Electrostatic Other Spray (specify)											
	B. Electrodeposition: Tank Dimensions ft. long X ft. wide X ft. high											
	Capacity gallons											
	C. Dip Tank D. Flow Coating											
	E. Roll Coating: Rotogravure Flexography Other (specify)											
	F. Brush											
	G. Other (describe)											
9)	If the construction date for the applicator is different than the construction date for the emission point, identify the construction start date for the applicator.											
10)	Mode of Surface Coating: A. Continuous Batch Other (specify)											
	B. Manual Automatic											
11)	Temperature of Coating Material as Applied:°F If the coated product goes to an oven, temperature of the oven°F											
12)	Maximum Coating Application Rate: Do not consider bottlenecks when answering. Other throughput limits can be identified in Item 13.											
	Applicator capacity (gal or lbs/hr)											
	Describe how the applicator capacity was determined.											
13)	Process Limitations:											
13)	Describe any limitations that make operation at the maximum capacity of the applicator or 8760 hours of operation impossible.											
14)	Release into Ambient Air:											
11)	Identify the stack or vent that the emissions enter the ambient air through:											
	Identify any control device (filter, incinerator, etc.) that is used to lower emissions from the applicator.											
	Describe stacks, vents, and control devices on form DEP7007N, Emissions, Stacks, and Controls Information.											

Commonwealth of Kentucky Natural Resources & Environmental Protection Cabinet Department for Environmental Protection

SECTION III COATINGS APPLIED

DIVISION FOR AIR QUALITY

DEP7007K

Continued

SURFACE COATING (OR) PRINTING OPERATION

	OATINGS as app								
	Emission Point #:								
$\mathbf{A}_{\mathbf{j}}$	Applicator #: Reference for the coating employed:								
O	Of all the coatings applied by this applicator, this coating will produce the highest emission rate of								
	Manufacturer's I.D. of all components in the coating (if the coating is applied as received from the manufacturer, only one I.D. should be provided):								
	the coating is a mas applied:	ixture, identify t	the ratio of the components:						
		lbs/gal	Highest emission rate pollutant content: lbs/gal or % (by weight)						
O	ther relevant coati	ing information	for this coating should be provided on a separate page as appropriate.						
Eı	mission Point #: _								
	pplicator #:		Reference for the coating employed:						
O	f all the coatings a	applied by this a	pplicator, this coating will produce the highest emission rate of						
	Manufacturer's I.D. of all components in the coating (if the coating is applied as received from the manufacturer, only one I.D. should be provided):								
If	the coating is a m	ixture, identify t	the ratio of the components:						
A	s applied:	-							
A	s applied:	-							
A: De	s applied: ensity:	lbs/gal							
As De	s applied: ensity:	lbs/gal	Highest emission rate pollutant content: lbs/gal or % (by weight)						
As Do	s applied: ensity: ther relevant coata mission Point #: _	lbs/gal	Highest emission rate pollutant content: lbs/gal or % (by weight) for this coating should be provided on a separate page as appropriate.						
As Do	s applied: ensity: ther relevant coata mission Point #: _ pplicator #:	lbs/gal ing information	Highest emission rate pollutant content: lbs/gal or % (by weight) for this coating should be provided on a separate page as appropriate. Reference for the coating employed:						
A: Do O: O: A:	s applied: ensity: ther relevant coata mission Point #: _ pplicator #:	lbs/gal ing information	Highest emission rate pollutant content: lbs/gal or % (by weight) for this coating should be provided on a separate page as appropriate.						
As Do	s applied: ensity: ther relevant coate mission Point #: _ pplicator #: _ f all the coatings a Ianufacturer's I.D.	lbs/gal ing information applied by this applied by the	Highest emission rate pollutant content: lbs/gal or % (by weight) for this coating should be provided on a separate page as appropriate. Reference for the coating employed: pplicator, this coating will produce the highest emission rate of nts in the coating (if the coating is applied as received from the manufacturer, only						
As Do	s applied: ensity: ther relevant coate mission Point #: _ pplicator #: _ f all the coatings a Ianufacturer's I.D.	lbs/gal ing information applied by this applied by the	Highest emission rate pollutant content: lbs/gal or % (by weight) for this coating should be provided on a separate page as appropriate. Reference for the coating employed: pplicator, this coating will produce the highest emission rate of ints in the coating (if the coating is applied as received from the manufacturer, only						
As Do	s applied: ensity: ther relevant coate mission Point #: _ pplicator #: _ f all the coatings a Ianufacturer's I.D. he I.D. should be p	lbs/gal ing information applied by this applied by this approvided):	Highest emission rate pollutant content: lbs/gal or % (by weight) for this coating should be provided on a separate page as appropriate. Reference for the coating employed: pplicator, this coating will produce the highest emission rate of nts in the coating (if the coating is applied as received from the manufacturer, only						
And Do	s applied: ensity: ther relevant coate mission Point #: _ pplicator #: _ f all the coatings a Ianufacturer's I.D. he I.D. should be p	lbs/gal ing information applied by this ap of all componer provided):	Highest emission rate pollutant content: lbs/gal or % (by weight) for this coating should be provided on a separate page as appropriate. Reference for the coating employed: pplicator, this coating will produce the highest emission rate of nts in the coating (if the coating is applied as received from the manufacturer, only						